



NOTE:

1. THIS DETAIL APPLIES TO LOCAL STREETS IN MULTI FAMILY RESIDENTIAL AREAS, AND COMMERCIAL AND INDUSTRIAL AREAS. FOR COLLECTOR STREETS USED FOR ACCESS TO THESE LAND USES INDICATED BY TRAFFIC PROJECTIONS SHOWN, USE STD. DETAIL RS-25.
2. AN APPROVED DRAINAGE SYSTEM IS REQUIRED WHERE THIS DETAIL IS USED.

- Ⓐ RIGHT-OF-WAY LINE AT OR ABOVE FLOOD CRITERIA
- Ⓑ CONCRETE SIDEWALK
- Ⓒ 6" CURB AND GUTTER
- Ⓓ ASPHALTIC CONCRETE SURFACE COURSE 2" THICK - S-III
- Ⓔ LEVEL LINE
- Ⓕ 8" THICK BASE COURSE, PRIMED ENTIRE WIDTH OF ASPHALT
- Ⓖ OFFSET FROM LEVEL LINE
- Ⓗ SOLID SOD
- Ⓘ 12" THICK STABILIZED SUBGRADE

STANDARD ROAD DETAIL
(60' R/W - 2 LANES CURB & GUTTER,
LOCAL STREET)
 N.T.S.